



U.S. Department
of Transportation

400 Seventh Street S.W.
Washington, D.C. 20590

**Pipeline and Hazardous
Materials Safety Administration**

October 11, 2006

Expiration Date: Oct 11, 2011

Mr. Kenneth Nevill
Chief Inspector
Pacific Scientific
11700 NW 102nd RD # 6
Miami, FL 33178

Dear Mr. Nevill:


The Office of Hazardous Materials Special Permits and Approvals has reviewed your application for approval as a cylinder requalification facility under Section 107.805 of Title 49 Code of Federal Regulations (49 CFR). At the recommendation of Arrowhead Industrial Services, Inc., this office is reissuing the requalifier identification number (RIN) **D019** to your facility at 11700 NW 102nd RD # 6, Miami, FL. This number applies to this location only and is valid until the posted expiration date above or until terminated by the Associate Administrator for Hazardous Materials Safety.

In addition to the requalification of cylinders under the relevant provisions of Sections 180.205 through 180.215 of 49 CFR, the following conditions must be met:

1. You must notify this office of any change in facility name, address, management, equipment or testing personnel within twenty days of the change.
2. Inspections and tests must be performed by, or in the presence of, a person who has been observed by the authorized inspector, or who has been added to your file by addition under condition number one (1) above.
3. A copy of this approval must be maintained adjacent to the testing unit.
4. This approval is renewable every five years.
5. Copies of your application and all supporting documentation must be retained and made available to DOT upon request.
6. Each "Hazmat employee", as defined in Section 171.8, who performs a function subject to this approval must receive appropriate training in accordance with Section 172.700 through 172.704.

7. All correspondence must include the requalifier identification number (RIN).

Approved by:

 Donald S. Hiltz
for Robert A. McGuire

Associate Administrator for
Hazardous Materials Safety